

Crystal Oscillator


Model Name NT3225SA Temperature-Compensated Crystal Oscillator (TCXO) NT3225S Series (with high-precision GPS supported)

Main Application

For mobile terminals with high-precision GPS functions

Features

- A crystal oscillator with highly stable frequency / temperature characteristics best suited for GPS.
- Supports low power supply voltage. (Supports DC +2.4±0.1 V to +3.5 V±5%.)
- Ultra-compact and light with a height, cubic volume, and weight of 1.0 mm max., 0.007 cm³, and 0.024g, respectively.
- Low power consumption.
- A surface-mount crystal oscillator. (Reflow soldering is possible.)
- Lead-free. Meets the requirements for re-flow profiling using lead-free solder.



Pb Free

RoHS Compliant
Directive 2002/95/EC

Specifications


Item	Model	NT3225SA
Standard nominal frequency (MHz)		16.367 to 27.456 MHz
Power supply voltage		+2.8V DC
Load		10kΩ//10pF
Consumption current		1.5mA max
Output level		0.8V(P-P) min (DC superimposition *1)
Frequency / temperature characteristic		±0.5×10 ⁻⁶ max
		-30 to +85°C
Power supply variation characteristics		±0.2×10 ⁻⁶ max/+2.8V±5%
Load variation characteristics		±0.2×10 ⁻⁶ max/(10kΩ//10pF)±10%
Aging		±1.0×10 ⁻⁶ max/year

Frequency setting conditions

1. Frequencies are set at normal temperatures (+25±2°C).
 2. Frequencies are set with a printed board that has a ground pattern attached to the underside of an oscillator.
 3. Connect the #1 terminal of the oscillator to the ground that comes with the oscillator.
- If you require a product with a different frequency, power supply voltage, frequency control characteristic, etc. to the standard specifications, please contact us with your enquiries.
 - Products with the AFC (Automatic Frequency Control) function are available. If you require such a product, please contact us.

*1. A DC-cut capacitor is not embedded in this crystal oscillator. Connect a DC-cut capacitor (1,000 pF) to the line-out terminal of the oscillator.

Dimensions



List of Ordering Codes

Frequency (MHz)	Ordering Code
16.367	NT3225SA-16.367M-NSA3401B
16.3676	NT3225SA-16.3676M-NSA3401B
16.368	NT3225SA-16.368M-NSA3401B
16.369	NT3225SA-16.369M-NSA3401B
16.8	NT3225SA-16.8M-NSA3401B
23.104	NT3225SA-23.104M-NSA3401B
24.5535	NT3225SA-24.5535M-NSA3401B
26	NT3225SA-26M-NSA3401B
27.456	NT3225SA-27.456M-NSA3401B

The above frequencies are NDK's standard frequencies. Frequencies other than the above are available. Feel free to contact our sales representatives.