# **Crystal Clock Oscillator**



# NZ2016SF

### **Ultralow Power Type**

#### **■** Application

 For Portable equipment (ex. Mobile Phone, Digital Media Player, PND, Notebook PC, etc)

#### **■** Features

- Ultralow power-driven (Min. +0.8V) crystal clock oscillator, ideal for mobile devices.
- Ultra compact and light. Dimensions: 2.0 x 1.6 x 0.7 mm, weight: 0.01 g.
- Wide frequency range: 1.5 to 50 MHz.
- Taped units enable automatic mounting and IR Reflow (lead free) is possible.
- · Lead-free.








Absolute maximum rating Supply Voltage (Vcc) –0.5 to +4.0 V Storage Temperature Range –55 to +125°C


### **■** Specifications

Item			Model	NZ2016SF		
Output Specification				CMOS		
Nominal Frequency Range			(MHz)	1.5 ≤ F ≤ 50		
Overall Frequency Tolerance			(×10 <sup>-6</sup> )	±50 ±30		
Operating Temperature Range			(°C)	-40 to +85 -10 to +70		
Supply Voltage			(V)	+0.9 to +1.5		
Current Consumption Max.	During Operation	+25 °C	(mA)	1.5 to 6.0		
	During Standby	+25 °C	(µA)	100		
Vol Max. / Voн Min.			(V)	0.1 Vcc / 0.9 Vcc		
Tr Max. / Tf Max.			(ns)	5/5		
Symmetry Min. to Max.			(%)	45 to 55		
Load (C <sub>L</sub> ) Max			(pF)	15		
Start-up Time Max			(ms)	4		
Standby Function				Available (Three-state)		
	1 V I					

#### **■** Dimensions



## ■ Output Waveform <CMOS>



#### **■** Standby Function

#1 Input	#3 Output
Level H (0.7 $V_{CC} \le V_{IH} \le V_{CC}$ ) or OPEN is selected.	Oscillation output ON
Level L (V <sub>IL</sub> ≤ 0.3 V <sub>CC</sub> ) is selected.	High impedance

# **Crystal Clock Oscillator**



# NZ2016SF

## **Ultralow Power Type**

#### **■** Specification Number

Overall Frequency	Operating Temperature	Supply Voltage (V)			
Tolerance	Range (°C)	+0.9±0.1	+1.2±0.1	+1.5±0.1	
±50×10 <sup>-6</sup>	-40 to +85	NSA3480E	NSA3481E	NSA3482E	
±30×10 <sup>-6</sup>	-10 to +70	NSA3480C	NSA3481C	NSA3482C	

Please specify the model name, frequency, and specification number when you order products. For further questions regarding specifications, please feel free to contact us.

Mar-2024