# **Crystal Clock Oscillator**



## NZ2520SF

## **Ultralow Power Type**

#### ■ Application

 For Portable equipment (ex. Mobile Phone, Digital Media Player, PND, Notebook PC, etc)

#### **■** Features

- Ultralow power-driven (Min. +0.8V) crystal clock oscillator, ideal for mobile devices.
- Compact and light. Dimensions: 2.5 x 2.0 x 0.9 mm, weight: 0.02 g.
- Wide frequency range: 1.5 to 50MHz
- Taped units enable automatic mounting and IR Reflow (lead free) is possible.
- · Lead-free.








Absolute maximum rating Supply Voltage (Vcc) -0.5 to +4.0 V Storage Temperature Range -55 to +125 °C


### **■** Specifications

Item			Model	NZ2520SF		
Output Specification				CMOS		
Nominal Frequency Range			(MHz)	1.5 ≤ F ≤ 50		
Overall Frequency Tolerance			(×10 <sup>-6</sup> )	±50	±30	
Operating Temperature Range			(°C)	-40 to +85	–10 to +70	
Supply Voltage			(V)	+0.9 to +1.5		
Current Consumption Max.	During Operation	+25 °C	(mA)	1.5 to 6.0		
	During Standby	+25 °C —	–(µA)			
Vol Max. / Voн Min.			(V)	0.1 Vcc/0.9 Vcc		
Tr Max. / Tf Max.			(ns)	5/5		
Symmetry Min. to Max.			(%)	45 to 55		
Load (C <sub>L</sub> ) Max.			(pF)	15		
Start-up Time Max.			(ms)	4		
Standby function				Available (Three-state)		

#### **■** Dimensions



## ■ Output Waveform <CMOS>



#### **■ Standby Function**

#1 Input	#3 Output	
Level H (0.7 V <sub>CC</sub> ≤ V <sub>IH</sub> ≤ V <sub>CC</sub> ) or OPEN is selected.	Oscillation output ON	
Level L (V <sub>IL</sub> ≤ 0.3 V <sub>CC</sub> ) is selected.	High impedance	

# **Crystal Clock Oscillator**



## NZ2520SF

## **Ultralow Power Type**

#### **■** Specification Number

Overall Frequency	Operating Temperature	Supply Voltage (V)			
Tolerance	Range(°C)	+0.9±0.1	+1.2±0.1	+1.5±0.1	
±50×10 <sup>-6</sup>	-40 to +85	NSA3468E	NSA3477E	NSA3469E	
±30×10 <sup>-6</sup>	-10 to +70	NSA3468C	NSA3477C	NSA3469C	

Please specify the model name, frequency, and specification number when you order products. For further questions regarding specifications, please feel free to contact us.

Mar-2024